

# EL<sup>®</sup>MARK

The Brand of Electricity

## RECESSED SPOTLIGHTS DL83TS SERIES

### GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 5W; 12W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 24°
- ∴ CRI: Ra≥80
- ∴ Power factor: 0.5
- ∴ Protection level against moisture and dust: IP65



### FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction

# TECHNICAL SPECIFICATION SHEET

[PRODUCT DETAILS »](#)

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Height (mm)	Diameter (mm)	Cut hole (mm)	Colour body
92DL83TS0530/WH	5	350	3000	80	72	62	white
92DL83TS0540/WH	5	350	4000	80	72	62	white
92DL83TS1230/WH	12	840	3000	93	92	62	white
92DL83TS1240/WH	12	840	4000	93	92	62	white

