

ELMARK[®]

The Brand of Electricity

RECESSED DOWN LIGHTS WITH HONEYCOMB COMB

GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 3W; 5W; 8W; 12W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 24°
- ∴ CRI: Ra≥80
- ∴ Efficiency: 70lm/W
- ∴ Protection level against moisture and dust: IP44



FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction




Honeycomb Anti-Glare

TECHNICAL SPECIFICATION SHEET

ELMARK[®]

The Brand of Electricity

Energy class: 

[PRODUCT DETAILS »](#)

Catalogue number	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height	Cut hole (mm)	Colour body
92DL84TS0330/WH	Round downlight	3	210	3000	45	37.5	40	white
92DL84TS0340/WH	Round downlight	3	210	4000	45	37.5	40	white
92DL84TS0530/WH	Round downlight	5	350	3000	60	51	55	white
92DL84TS0540/WH	Round downlight	5	350	4000	60	51	55	white
92DL84TS0830/WH	Round downlight	8	560	3000	74	66.5	65	white
92DL84TS0840/WH	Round downlight	8	560	4000	74	66.5	65	white
92DL84TS1230/WH	Round downlight	12	840	3000	84	75.5	75	white
92DL84TS1240/WH	Round downlight	12	840	4000	84	75.5	75	white

 **RoHS**
COMPLIANT 