

EL[®]MARK

The Brand of Electricity

RECESSED DOWN LIGHTS

92EL62 IP44

GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 13W; 20W; 30W; 42W
- ∴ LED source: SMD 2835
- ∴ Colour temperature: 3000K; 4000K; 6500K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 60° 70° 75°
- ∴ CRI: Ra≥80
- ∴ Power factor: 0.5
- ∴ Protection level against moisture and dust: IP44

FEATURES »


- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction



PRODUCT DETAILS »

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Efficiency (lm/W)	Colour body	Cut size (mm)
92EL62281330/WH	13	1080	3000	83	white	100
92EL62281340/WH	13	1080	4000	83	white	100
92EL62281365/WH	13	1080	6500	83	white	100
92EL62282030/WH	20	1800	3000	90	white	140
92EL62282040/WH	20	1800	4000	90	white	140
92EL62282065/WH	20	1800	6500	90	white	140
92EL62283030/WH	30	3000	3000	100	white	170
92EL62283040/WH	30	3000	4000	100	white	170
92EL62283065/WH	30	3000	6500	100	white	170
92EL62284230/WH	42	4200	3000	100	white	205
92EL62284240/WH	42	4200	4000	100	white	205
92EL62284265/WH	42	4200	6500	100	white	205

Catalogue number	Deep (mm)	Height (mm)
92EL62281330/WH	120	120
92EL62281340/WH	120	120
92EL62281365/WH	120	120
92EL62282030/WH	160	160
92EL62282040/WH	160	160
92EL62282065/WH	160	160
92EL62283030/WH	185	185
92EL62283040/WH	185	185
92EL62283065/WH	185	185
92EL62284230/WH	217	217
92EL62284240/WH	217	217
92EL62284265/WH	217	217



CE RoHS COMPLIANT 