


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM2040/WH		
POWER: 20W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1525.8 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1949	1975	1943	1890	1850	1825	1832	1873	0- 10	200.6	200.6	13.1
20	1259	1284	1271	1232	1201	1178	1181	1204	10- 20	428.1	628.6	41.2
30	707.0	729.6	758.3	749.4	735.9	714.6	694.2	676.0	20- 30	437.7	1066	69.9
40	288.0	332.7	360.3	348.8	323.6	272.2	244.8	250.3	30- 40	338.2	1405	92.1
50	32.04	38.39	42.91	39.28	32.70	28.15	25.87	26.99	40- 50	88.35	1493	97.8
60	13.75	14.21	15.19	15.08	14.25	13.47	13.58	13.47	50- 60	18.43	1511	99
70	7.359	7.828	7.376	7.474	7.142	6.863	6.971	6.774	60- 70	10.39	1522	99.7
80	0.5861	0.6394	0.7437	0.8005	0.6140	0.5674	0.5331	0.5067	70- 80	3.844	1526	100
90	0.0623	0.0584	0.0572	0.0614	0.0975	0.0924	0.0981	0.0928	80- 90	0.2776	1526	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:24 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```