


LAMP PHOTOMETRIC REPORT

MODEL: 93TL206750WW/BL		
POWER: 50W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5265.3 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2434	2421	2399	2388	2386	2391	2406	2424	0- 10	228.8	228.8	4.35
20	2470	2487	2435	2434	2407	2438	2439	2493	10- 20	689.6	918.3	17.4
30	2173	2397	2228	2370	2197	2354	2179	2393	20- 30	1109	2027	38.5
40	1407	1782	1513	1816	1505	1767	1431	1769	30- 40	1237	3265	62
50	748.3	955.0	801.8	997.5	818.7	956.5	755.6	940.2	40- 50	934.9	4200	79.8
60	417.3	454.3	415.4	472.9	451.8	459.0	395.0	443.5	50- 60	557.9	4757	90.4
70	240.4	214.8	206.4	220.3	254.7	217.0	196.1	208.2	60- 70	313.5	5071	96.3
80	108.0	79.31	76.33	79.84	114.3	77.70	68.97	75.43	70- 80	155.8	5227	99.3
90	1.757	1.680	1.487	1.605	1.618	1.394	1.269	1.430	80- 90	38.56	5265	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```