

ELMARK[®]

The Brand of Electricity

LED GLOBE PMMA CLEAR



TECHNICAL SPECIFICATION

OUTDOOR- GARDEN

ELMARK[®]

The Brand of Electricity

Technical data:

- Rated voltage: 230VAC
- Power: 18W; 20W; 30W; 40W
- Lamp holder: E27
- Colour temperature: 4000K
- Diffuser: PMMA (polymethyl methacrylate)
- Metal pole: $\Phi 60$
- Colour: clear
- Colour rendering index: Ra \geq 80
- Switch on/off > 15 000
- Average Lifetime: 30 000h
- Dust and humidity protection level: IP65
- Protection against electric shock: I
- Surface requirements: Class F

Features:

- Wide distribution of even and stable light
- Economic- low power consumption
- Repeated switch on/off does not effect the fixture lifespan
- Instant light at maximum luminous flux
- Environmentally friendly - no mercury and lead
- No ultraviolet and infrared rays
- Resistant to shock and vibration stable body

Area of application:

- Suitable for outdoor use
- Parks
- Balcony
- Gardens


TECHNICAL SPECIFICATION

OUTDOOR- GARDEN

ELMARK®

The Brand of Electricity


Variants and Dimensions:



Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour aluminium ring	Size (mm)		
					Diameter	Width	Height
96400023A60LED	18	1700	4000	clear	200	100	210
96400024G95LED	20	1800	4000	clear	250	125	260
96400025G95LED	20	1800	4000	clear	300	145	310
9640002730LED	30	2700	4000	clear	400	220	410
9640002740LED	40	3600	4000	clear	400	220	410

96400023A60LED

ELMARK
lighting

 This luminaire is compatible with bulbs of the energy classes:

A⁺⁺

A⁺

A


~~B~~

~~C~~

~~D~~


~~E~~

}



The luminaire is sold with a bulb of the energy class:

A⁺



874/2012

EN 55015 • EN 61000-3-2 • EN 61000-3-3 • EN 61547 • EN 60598-1 • EN 60598-2-2 • EN 50581:2012



www.elmarkholding.eu